

PLOWING FORWARD

KAGE QUALITY GUARANTEE

When you purchase a KAGE product, we want you to be confident you're buying the best equipment possible. We back our products with a 15-day trial guarantee. From the date of delivery, you have 15 days to try out the product and if you're not satisfied, you can return it - no questions asked. KAGE will reimburse 100% of the purchase & shipping

BUILDING IT BETTER

If the idea isn't revolutionary or innovative as our company name states, we're not taking the idea far enough. KAGE Innovation invents and manufacturers equipment for the professional grounds manager. Our core objective is to offer new products as solutions to common industry setbacks. In short, we're always on the lookout for "the better way."

WHAT'S IMPORTANT

Our customers and employees.

KAGE Innovation is run by people, and we serve people. The company was started because of an opportunity that was seized. KAGE Innovation continues to create opportunities for people - both customers and employees alike.

DRIVING NEW IDEAS TO THE INDUSTRY

Have you ever thought, "There just has to be a better way!" Applying our Experience Driven Innovation to conquer those ideas is what we do. Every week new ideas are hashed out and the ones that make it earn the KAGE stamp for excellence in design.

As our business has flourished, our mindset has not changed. It is still much like when I started out tinkering in my dad's workshop 12 years ago. Persevering until we find the better way, and designing with the end-user in mind. As we grow and the number of KAGE employees grow, our collective vision can be summed up in one sentence; "We want to make it easy for you".

Ours is a timeless industry. Timeless because there has, and always will be, grass to mow and snow to push. The caveat is that time is of the essence. In this industry the only variable is time, and we all need more of it. Time is expensive, and as labor costs increase we're pushed to work smarter and faster. It's this void where we seek to make the difference

"Whatever you do, work heartily, as for the Lord and not for men" - Colossians 3:23

CONTENTS

Snow Systems

- 3 SnowFire/Skidsteers
- 5 SnowFire/Compacts
- SnowStorm
- 9 ShadowBlade

AG Mounts

11 Tractor Mounts

Snow Tires

13 KageKlawz

Anti-Icina

15 LiquidRage

Flexible Cutting Edge System

17 AdvantEdge

Lawn Management

19 WheelKaddy

Snow Management

- 71 Snow Stakes
- 21 BuddyStrap
- 22 Poly Rotor Paddles
- 22 SnowBlaze Shovel

Plow Accessories

- 23 Curb Guard Kit
- 23 Polyurethane Cutting Edge Kit
- 23 Back Drag Kit
- 23 Plow Guides
- 24 WingLine™ Laser Plow Guide

Specifications

- 25 SnowFire/Skidsteer/Compacts Specs
- 26 SnowStorm Specs
- 27 SnowFire Quick Connect Specs
- 28 SnowStorm Quick Connect Specs
- 29 ShadowBlade Specs
- 30 Tractor Mounts Specs
- 31 KageKlawz Specs
- 32 LiquidRage Specs
- 33 AdvantEdge Specs
- 34 WheelKaddy Specs

LEGEND








Compact Wheel Loader





Compact Loader Backhoe





3-Point Tractor



Rear 3-Point Tractor



Municipal Truck



Commercial Walk-Rehind Mower

SNOWFIRE/SKIDSTEER SNOW PLOW SYSTEM PATENT PROTECTED

BULLET PROOF STRUCTURE



THE BLADE

>Plow structure like no other in its class with an attack angle of 65 degrees

>Moldboard sheet itself is built with 10-guage GRADE 50 steel to extend the life of the plaw

>Blade features a standard 8" safety trip-edge that prevents accidental damage when encountering hidden obstacles by tripping back 68 degrees



THE BOX

>Bullet proof structure that conquers the destructive tendencies of any snow removal operation

>Self-adjusting, flexible polyurethane skids. They have the ability to slide upwards as the cutting edge of the plaw becomes worn, allowing it to cleanly scrape the plowing surface

>10" wide snow catches to prevent spillage while pushing



UNIVERSAL SKIDSTEER MOUNT

The Universal Skidsteer Mount is the standard for the SnowFire System. This couples to any modern skidsteer in seconds. Then, just couple the hydraulic couplers to the machine auxiliary hydraulic and you are ready to roll snow!



FROM BOX TO BLADE IN SECONDS

The SnowKage Box hooks onto a skidsteer snow plow to instantly create a revolutionary containment system. This is done in seconds without leaving the cab - no pins, bolts or hinges.

Attaching & detaching the box can take less than 5 seconds for a skilled operator to do.









SNOWFIRE/COMPACTS SNOW PLOW SYSTEM PATENT PROTECTED

OVERBUILT BY DESIGN



MULTIPLE CARRIER ATTACHMENTS

This system can incorporate many different styles of hook-and-pin style attachments OR universal skidsteer attachments. See attachment options on page 27.



FLOATING TOP LINK

Uniquely designed for compact wheel loader applications, this attachment allows the plow to float while driving over uneven terrain. This hitch style is recommended for all wheel loader applications because it increases the ability to steer the loader, and the scraping ability of the plow. For available Quick Attaches see our specification tab.



SNOW PUSHER CAM

The simple and sturdy way to attach the SnowKage to the blade from inside your skidsteer cab is by using a cam locks. Raise the boom up and tilt the plow down behind the hooks of the SnowKage, align cam lock brackets of the blade with the receptor hooks of the SnowKage and raise the boom.... then back to work! This is done in about 5 seconds. Back and forth from plowing to pushing.




THE PAYOFF

>Reduce plow time by 25% to 50%

>Advantages of a snow plow and a pusher box combining them into one fast and seamless operation

>Windrow or back drag with the plow normally, then grab the box to push out their piles or windrows









MOVE MOUNTAINS



OPTIONAL LASER GUIDANCE

The optional laser guidance reminds the operator when the ShadowBlade is deployed off to either side.



3-POINT SNOW ATTACK

We're building our reputation on being an innovator for the snow-removal industry. The ShadowBlade is a patented 3-point rear attachment design. This new weapon will set your tractor up to be a worthwhile year-round investment.



SIMPLE JOYSTICK CONTROL

Simple joystick control eases the operators ability to control both front and rear plow systems.



HYDRAULIC VALVE CIRCUIT


Located at the rear of the tractor up high for easy access, the hydraulic valve circuit, stays clear of compacted snow.





TO ORDER CALL 651-433-4628, OR GO ONLINE: KAGEINNOVATION.COM

TRACTOR MOUNTS BOLT-ON UNDERCARRIAGES



REVOLUTIONARY DESIGN

Let's have a conversation about the fuel efficiency of a tractor, the maneuverability of a tractor, the comforts of a tractor cab, and the superior traction and power of a tractor.

Then let's talk about mounting the world's best plow on the front of that tractor. Now that's something worth talking about! KAGE has harnessed the versatility of using a tractor for snow plowing by designing a bolt-on undercarriage mount for their signature plow systems. Our tractor mounts are built to handle the rigors of massive snow removal.



MORE VISIBILITY

With the low profile attachment of the KAGE Plow System and the undercarriage, the tractor and plow are more maneuverable and visibility is vastly improved over the use of loader arms.

FLOAT MODE

Maintain full down pressure while still easily plowing over contoured surfaces with the float mode.

KAGE.









WHEELKADDY

SNOWSTORM

SHADOWBLADE

TRACTOR MOUNTS

KAGEKLAWZ

LIQUIDRAGE

ADVANTEDGE

SNOW Management

LESS SPIN, MORE DRIVE



HORSEPOWER'S NOT THE ISSUE

We've done the side by side tests and there's no comparison in performance between conventional skidsteer tires and the KageKlawz. Even in a downward sloped drive, the results were obvious - the traction of the KageKlawz proved to be the game changer for skidsteer snow removal. You have all the power you need, now you just to put it to better use.

RADIAL VS BIAS TECHNOLOGY

MICHELIN® XM+S4 Pre-mold Retread Tires are the best performing snow tire tread on the market. They come with a Tread-Life Warranty* serviceable at any Michelin Retread dealer near you which will minimize down time and with retreads, you may never need to buy a set of replacement tires again.

or down to 2/32 which is the legal limit. Search on-line for a certified



MICHELIN XM+S4 RETREADS

These tires allow the machine to transfer more power to the ground and absorbs more shock from uneven surfaces.



PROTECTED **VALVE SYSTEM**

Wheels come standard with welded valve protector.



TO ORDER CALL 651-433-4628, OR GO ONLINE: KAGEINNOVATION.COM

ADVANTEDGE

SNOWSTORM

SHADOWBLADE

TRACTOR MOUNTS

KAGEKLAWZ

LIQUIDRAGE

WHEELKADDY

SNOW Management

LESS ICE, CLEANER SURFACE



TOP 10 REASONS TO USE LIQUID ICE CONTROL

1. Liquid products are better for turf, soil, and ground water

- 2. Liquids do not bounce off your target coverage area
- 3. Liquid anti-ice applications do not 'plow off'
- 4. Liquids almost completely eliminate tracking into buildings and reduce corrosion and build up
- 5. Liquid anti-icing applications prevent ice bonding to the pavement
- 6. Liquids are easier to pump than dry salt is to scoop
- 7. Liquid blended products include corrosion inhibitors which lengthens equipment life
- 8. It takes 10x more resources to post de-ice than pretreat with liquid
- 9. Dry salt stops working at 10-15 degrees F
- 10. It takes 20 minutes for dry salt to start working at 25 degrees F





ADVANTAGES AND FEATURES

Anti-Icing liquids are becoming all the rage. Use fewer solids to get the job done, and provide your customers with top-notch service.

The LiquidRage enables you to apply brine and other chemicals from your skidsteer or tractor, without the need to buy expensive adapters and other equipment.

Features:

Adaptable to skidsteers and ag tractors (universal skidsteer attachment, CAT II 3-Point Hitch attachment)

>Fully enclosed design protects critical components >150 gallon capacity





TO ORDER CALL 651-433-4628, OR GO ONLINE: KAGEINNOVATION.COM

LiquidRage

SNOWFIRE/ SKIDSTEER

SNOWSTORM

SHADOWBLADE

TRACTOR MOUNTS

UNIVERSAL MOUNT



FRONT AND WING **BLADE FLEX EDGE** SYSTEM

Until now, sectional plows and cutting edges have only been available on a few brands of plows. The AdvantEdge™ makes it possible to harness sectional cutting edge technology on almost any plow or pusher available on the market today!

17





REDUCES DAMAGE TO PLOWED SURFACES

The AdvantEdge reduces the damage to curbs, asphalt/ concrete transitions all while scraping better!

Each 18" or 24" cutting edge section is milled from the proprietary Hardox™ wear-plate, common to the mining industry for abrasion resistance and strength. Compared to carbide cutting edges, Hardox is not as brittle, and does not require any additional backing plates.



AUTOMATICALLY **NAVIGATES PEAKS AND DEPRESSIONS**

No pavement is perfectly flat, so unless your cutting edge is flexible, you're leaving snow behind. The independent cutting edge sections of the AdvantEdge help the blade to contour to the shape of any surface. The more snow you can remove during your plowing operations, the less salt and sand usage you'll have.

PRESSURE ADJUSTABLE **ENCAPSULATED** DESIGN

This patent pending design gives you the flexibility to adjust the pressure on each section so you can obtain just the right amount of preload. Each section is equipped with multiple 120 lb/inch die springs. AdvantEdge uses a closed face design reducing the impact that salt, sand, and ice can have. Each section is completely covered by the cutting edge, which is easily replaced by removing two bolts.





SNOWFIRE/ SKIDSTEER

SNOWSTORM SHADOWBLADE

TRACTOR MOUNTS

KAGEKLAWZ

ADVANTEDGE

WHEELKADDY

SNOW Management

WHEELKADDY COMMERCIAL MOWER SULKY

COMMERCIAL GRADE

SULKY

We designed the KAGE WheelKaddy with two things in mind: Increased life expectancy, and reduced down time. That is why this sulky utilizes automotive-grade components, such as tapered roller bearings, drive-train (PTO) pivot yokes, and a grade 50 steel platform. Experience less down time plus a more comfortable ride because of our designed-by-the-user approach!



The original. Simple,

500 SERIES

yet packed with features and as durable as they come! The 500 series features a very smooth ride with the unique suspension.

250 SERIES


Simple and durable.

The economic model

that gives you the

lowest maintenance

sulky ever.



360 degrees for backing up without damaging turf. This model features suspension, longevity, and full 360 degree range of motion.

The 360 Series swings



TO ORDER CALL 651-433-4628, OR GO ONLINE: KAGEINNOVATION.COM

SNOWSTORM SHADOWBLADE

TRACTOR MOUNTS

KAGEKLAWZ

LIQUIDRAGE

ADVANTEDGE

WHEELKADDY

SNOW MANAGEMENT



SNOW STAKE SYSTEM

STAY ON TRACK ALL SEASON

KAGE developed this Pounder & Quiver Kit to address the shortcomings of conventional snow stakes. The KAGE Pounder punches a perfect hole for the marker stake. The 3 lb. slide hammer can punch through the toughest soils and even road base gravel.

The Quiver features high-quality nylon material and carries 120 stakes up to 32" long. Strap the quiver to your leg and waist using the two 2" wide straps and industrial strength buckles.

Our Snow Plow Stakes are made of a durable polymer blend which readily rebounds after impact, even in sub-zero temperatures. Available in 26", 32" and 36" lengths.

Replacement tips are available.





BUDDYSTRAP

MINIMIZE BACK STRAIN

The BuddyStrap includes many features that make what was previously a chore, fun! A major benefit of the strap is that it's universal, so you can enhance any D-handled snow shovel in 5 minutes, saving you time, money, and back strain.

Simply attach the strap to the shovel and you can sling it over your shoulder for hands-free carrying. For highspeed commercial applications, the one-handed on and off design allows for easy access.

The strap does not interfere with stacking or storage, so when it's time to put your shovel away, you can do so with ease. The durable seatbelt material resists damage and abuse, and with reinforced stitching and grommets, the heavy duty strap won't tear or weather.





POLY ROTOR PADDLES

KICK MORE SNOW... LONGER

Single-stage snow blowers are a crucial part of your snow removal business. It's hard enough to keep them maintained without the frequent paddle and scraper bar replacement due to normal wear. Compared to rubber paddles, Poly Rotor Blades last up to 4 times longer, produce a cleaner wear edge and sell for the same price.

Keeps its edge as it wears, cutting down to the pavement and cleaning more efficiently.







SNOWBLAZE SHOVEL

CLEAR SNOW MORE EFFICIENTLY

The SnowBlaze revolutionizes the way that commercial contractors and home-owners alike are able to remove mass quantities of snow. Clearing long stretches of sidewalk, or even driveways is easiest if you can 'windrow' the snow. By 'plowing' the snow to one side while pushing it forward, you are displacing the snow in two



directions, and containing the dribbles to one side. The flip-stick used for windrowing tucks up and out of the way when not in use and does not interfere with pushing, back-dragging, or lifting the snow.

Utilizes a steel cutting edge that is easily removable and replaceable. It is also supported by an aluminum backing bar to help keep the edge straight.





POLYURETHANE CUTTING EDGE

The Polyurethane Cutting Edge is useful when plowing delicate surfaces such as decorative concrete and pavers, or seal-coating. In our experience, this proprietary blend of polyurethanes outlasts rubber, and even steel in some cases without damaging the plowing surface. The blade is 1 ½ inches thick, predrilled and the optional kit comes with a steel support strip and extra long carriage bolts for easy installation.



BACK DRAG KIT

The Back Drag Kit manufactured exclusively by KAGE Innovation is designed to fit any 6" to 8" snow plow cutting edge machine with a highway punch bolt hole pattern. It also works great with trip-edge plows and when you're angling snow away from curbs.

The entire kit weighs 10 pounds and it's built from the same uniquely blended polyurethane material used in our Poly Cutting Edges and Poly Skids. It's far more durable and will last considerably longer than rubber.





PLOW GUIDE

High visibility plow guides keep you on track during plow time and helps prevent landscape and curb damage. Easy to replace and universal to all KAGE plows.





impact design, the laser plow quide is easy to install and will help protect your equipment and operators for years to come.

The KAGE Advantage:

- >Easy to install
- >Inexpensive
- >Reduce plow damage and downtime

CURB-GUARD KIT

Optional curb guard

kit helps reduce wear

to the trip edge. Clean

curb lines are crucial,

but don't wear out your

plow in the process! The

curb quards are sold as

a kit, and they are able to

transpose so that you get

double the wear.


SNOWFIRE SPECS


SNOWSTORM SPECS


			3 100 100 100 100		
SNOWBLADE					
For Machines Weighing 5,000 lbs.	SB72/LB72	SB96/LB96	SB108/LB108	SB120/LB120	SB144/LB144
Blade Width	6'	8'	9'	10'	12'
Blade Width at Full Angle	59"	79"	88-1/2"	98-1/4"	125"
Oscillation (Degrees/Inch) Each End	6° / 7-1/2"	6° / 10"	6° / 11-1/4"	6° / 12-1/2"	6° / 15″
Moldboard Radius			15-1/2"		
Moldboard Gauge/Steel Grade		10	3 gals. / Grade	50	
Universal Skid Steer Attachment Guide			Standard		
Trip Springs	4 Compression	4 Compression	4 Compression	4 Compression	8 Compression
Machine Size Recommendation	5,000 +	6,000 +	6,500 +	7,000 +	9,000 +
Cutting Edge		5/	8" x 6" High Ca	rbon	
Cross-Over Relief Valve			Standard		
Pivot Frame Length	Shortened (25")		Standard L	ength (31")	
Weight	906 lbs.	1,031 lbs.	1,087 lbs.	1,147 lbs.	1,651 lbs.
Cylinders	1-1/2" Rod	1-1/2" Rod	1-1/2" Rod	1-1/2" Rod	2" Rod
Blade Height			31-1/8"		

SNOWKAGE					
For Machines Weighing 5,000 lbs.	SB72/LB72	SB96/LB96	SB108/LB108	SB120/LB120	SB144/LB144
Overall Height			36 3/4"		
Overall Width	80"	104"	116"	128"	151-1/2"
Replacement Side Panels			YES		
Hook Thickness (Skid Steer Only)			1-1/2"		
Replacement Polyurethane Skids			Yes		
Unit Weight	366 lbs.		44	2 lb.	
Machine Size Recommendation	5,000 +	6,000 +	6,500 +	7,000 +	9,000 +
Overall Width at 35° Angle	85-5/8"	105-3/8"	115-1/4"	125-1/8"	144-3/4"

Total Weight (Blade & Box)	1,272 lbs.	1,473 lbs.	1,529 lbs.	1,589 lbs.	2,093 lbs.
For Machines Weighing 5,000 lbs.	SBK72/LBK72	SBK96/LBK96	SBK108/LBK108	SBK120/LBK120	SBK144/LBK14
SNOWFIRE SYSTEM					










SNOWBLADE					
For Machines Weighing 15,000-30,000 lbs.	KBSS10	KBSS12	KBSS14		
Blade Width	10'	12'	14'		
Angle		36 Degrees			
Blade Width at Full Angle	97"	116-1/2"	136"		
Oscillation (Degrees/Inch) Each End	6° / 12-1/2"	6° / 15"	6° / 17-1/2″		
Moldboard Gauge/Steel Grade	1	0 gals. / Grade 5	0		
Loader Quick Attach		See Page 28			
Trip Springs		8 Compressions			
Cutting Edge	(2 pc.) 5/8" x 8" x 5'	(2 pc.) 5/8" x 8" x 6'	(2 pc.) 5/8" x 8" x 7'		
Hydraulic Cross-Over Relief Valve		Standard			
Pivot Frame Length		48"			
Weight	2,282 lbs.	2,375 lbs.	2,468 lbs.		
Cylinders (2)	(2)) 3" Bore 1-1/2" R	lad		
Blade Height	36"				
Electric/Hydraulic Valve Kit		12V/24V			

SNOWKAGE			
For Machines Weighing 15,000-30,000 lbs.	KBSS10	KBSS12	KBSS14
Overall Height		40"	
Overall Width	143"	155"	179-1/2"
Overall Width at Full Angle	131"	150-1/2"	169-3/4"
Approximate Capacity	12 yds. +	14 yds. +	18 yds. +
Replaceable Polyurethane Skids		2" x 10" x 42"	

Total Weight (Blade & Box)	3.088 lbs.	3.181 lbs.	3.274 lbs.
For Machines Weighing 15,000-30,000 lbs.	KBSS10-XL	KBSS12-XL	KBSS14-XL
SNOWSTORM SYSTEM			








SNOWFIRE QUICK ATTACH SPECS


SNOWSTORM QUICK ATTACH SPECS


SNOWFIRE QUICK ATTACH DIMENSIONS									
Coupler	KAGE Part #	A (in inches)	B (in inches)	C (in inches)	D (in inches)	E (in inches)	X (in inches)	Y (in inches)	Z (in inches)
CAT IT28	28-10	21.875	1.125	2.520	19.937	2.063			
JCB 212	212	25.188	1.000	2.280	19.209	1.760	33.750		
John Deere 310	JD310	38.00	1.000	2.596	20.321	1.825			
JCB 409	409	35.125	1.000	1.650	12.289	1.590			
Takeuchi	TAK506580	37.250	1.125	1.580	12.200	1.580	33.126	1.580	19.690
Case 221	221	9.250	1.000	2.000	20.174	2.025	42.00		
FFC	FFC	47.500	1.000	2.066	24.498	2.060			
JCB 535	535-10	40.375	1.000	2.410	23.652	1.509		211	
Komatsu WB140	WB140	29.375	1.000	2.030	17.687	1.810			
Valva 356-20	356-30	39.375	1.000	2.420	24.187	2.000			
New Holland Euro	845	30.250	1.000	1.650	11.750	.920			
Universal Coupler	28-600	-	-	-	-	-			


X: Marks additional width dimensions for ears on different planes then the main ears



SNOWSTORM QUICK A	TTACH DIMENSIONS							
Quick Attach	KAGE Part #	A (in inches)	B (in inches)	C (in inches)	D (in inches)	E (in inches)	X (in inches)	Non Stocked Additional Cost
JRB 416	JRB-416	30.628	1.500	3.001	16.281	2.126		
CAT Fusion	CATFUSION	22.875	1.500	5.000	24.625	3.376		
CAT IT28	CATIT28F-K	22.250	1.500	2.520	19.937	2.062		
Valva	356-1	39.360	1.000	2.420	24.260	2.000		
Hyundai	HL740TM	22.287	1.500	2.461	19.770	1.992		
Terex	TERSKI863	34.250	4.000	1.969	19.860	2.362	39.250	
JCB 541	JCB54ISS	42.484	1.500	2.266	23.687	1.265		
Bobcat 723	BBTC-723	31.250	1.000	3.250	22.437	1.275		
JCB 535	535-200	40.625	1.250	2.437	23.625	1.500		
JRB 418	JRB-418	32.750	1.500	3.030	20.670	2.060		Yes
CAT IT38	CATIT-38	36.250	1.500	3.090	22.790	2.060		Yes
Hi Viz	544HV	39.120	1.500	2.440	24.280	2.064		Yes
ACS 1000/2000	QA90006150							Yes








116.5"			100
Optimum Plow Angle For Win		XX	300
Angle For Win	S Comments		
+	5' 9"		-
	Optimum Plowing Angle For Wing		3
	Angle For Wing	O. T.	門.
4' 3"			
Optimum Plow Angle For Win			1
Angle For Will			
	37.0 ° Optimum Plowing		
	Angle For Wing		
	•		
	17.4°		
	Optimum Plowing		
	Angle For Wing		
		\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	
traight Wing		41	
xtensions re also availab			
ic also available			
	108" Optimum Plov	ving W	
	Angle For Win	19	
5.89 ° otimum Plowing		A	
ngle For Wing		0	
E			
	11' 1'		
	Optin	num Plowing	
otimum Plowing	→ 9' 7" —	e For Wing	
ngle For Wing	Optimum Plowing Angle For Wing	Optimum	Plowing
0		Angle Fo	

Make/Model Tractor	Plow Hitch Style	Lift Cylinders	Tractor Requirements	Recommended System				
John Deere ® - 6430/6125R/6125M/6115M			Loader Valve/Joystick in Cab	10', 12', 14' SS				
John Deere ® - 6410M/6150M			One Auxiliary (mid or rear)					
John Deere ® - 5095M/5105M/5100M/5115M/5085M			Loader Valve/Joystick in Cab	10' SS or 12' SF				
John Deere [®] - 5101E/5083E/5085E*	Cat II 3-Point	(2) 3"x10"	One Auxiliary (mid or rear)					
lohn Deere [®] - 5075E		800-1,000 Lbs Count	800-1,000 Lbs Counterweight Recommended	6′, 8′, 9′, 10′, 12′ SF or 10′ SS				
John Deere 🛭 - 6101D/6115D/6130D/6140D **			Joystick in Cab	4D/ 4D/ 4// DD				
lohn Deere 🛭 - 6105D/6140D		0	One Auxiliary (mid or rear)	10', 12', 14' SS				
(UBOTA [®] - L4240/L4740/L5040/L5240/L5740/L6060			Level to Cal W/2-d Angleson Dates	8' SF				
IOHN DEERE® - 4120/4320/4520/4720	7-Pin Style	2-Pin Style	2-Pin Style	2-Pin Style	2-Pin Style	(1) 2-1/2″x16 Cylinders	Joystick in Cab W/3rd Auxiliary Option 800-1,000 Lbs Counterweight Recommended	ם מר
OHN DEERE® - 4066R			and the second s	6' SF				
UBOTA [®] - M8540/M9540/M8560/M9960/M5				10' SS or 12' SF				
(UBOTA® MI35X			Loader Valve/Joystick in Cab					
CUBOTA [®] M110GX	Cat II 3-Point	(2) 3"x10"	One Auxiliary (mid or rear)	10', 12', 14' SS				
UBOTA [®] M135GX/MG	Cat II 3-Point	^{It} Cylinders	Cat II 3-Point Cylinders					
Iniversal Kit (requires end-user fabrication)			Loader Valve/Joystick in Cab One Auxiliary (mid or rear) 800-1,000 Lbs Counterweight Recommended	8', 9', 10', 12' SF or 10', 12' S				



5 1/8 O

SNOWSTORM SPECS

SNOWFIRE QUICK
ATTACH SPECS

SNOWSTORM QUICK ATTACH SPECS

SHADOWBLADE SPECS

KAGEKLAWZ SPECS

LIQUIDRAGE SPECS

LIQUIDRAGE SPECS

KAGEKLAWZ APPLICATII	ON GUIDE							
		STOCK T	IRE SIZE					
10 x 16.5 (stock tire is about 30-32" tall) 12 x 16.5 (stock tire is about 33" tall)								
KAGE KLAWZ MODELS								
225 Kit	245 Kit*	255 Kit**	245 Kit	255 Kit*				
		FENDER INT	ERFERENCE					
3" Fender Clea	orance Required	6" Fender Clearance Required	3" Fender Clearance Required					
SPEED ENHANCEMENT								
No Significant Increase	11% Increase (~1.5 mph)	11% Increase (~2.1 mph)	No Significant Increase	11% Increase (~2.1 mph)				


^{*}NOTE: This configuration increases the overall height of the machine by approximately 1.5"


**NOTE: This configuration increases the overall height of the machine by approximately 3"

KAGEKLAWZ SPECIFICATIONS				
SNOW TIRE KIT	Model 225	Model 245*	Model 255	Model 255**
Size	225/70R19.5	245/70R19.5	255/70R22.5	255/70R22.5
Ply Rating / Load Range	12	14	16	16
Capacity Per Set of 4	14,560 lbs.	18,160 lbs.	22,040 lbs.	22,040 lbs.
Pilot Hole Diameter	6"	6"	6"	9" - Bobcat Specific
Bolt Pattern	8 x 8"	8 x 8"	8 x 8"	8 x 10.25"
Wheel Size	19.5 x 6.75	19.5 x 6.75	22.5 x 8.25	22.5 x 8.25
Tire Height	32.4	33.4	36.6	36.6
Overall Tire Width	8.8	9.6	9.8	9.8
Offset	POS 1.25"	POS 1.25"	NEG 1.5"	ZERO
Tread Width	7.1	7.5	7.8	7.8
Product Number	225KIT	245KIT	255KIT	255LGKIT


^{*}NOTE: Most common tire kit

^{**}NOTE: Bobcat Specific (\$750, \$770, \$850, A300)





LIQUIDRAGE	
Specifications	
Maunts	Skid Steer/Cat II 3-Point
Pump	Hydraulic
Internal Debris Filter	Standard
Dump Valve	Standard
Quick Disconnect Hydraulic Couplers	Skid Steer Flat Face Standard
Quick Disconnect Ag Hydraulic Couplers	EXTRA
Nozzle Type	(5) 6 Stream Penetrating Nozzles
Tank Capacity	150 gals.
Pressure Regulator with Gauge	Standard/Manual
Spray Width	Adjustable 5' - 10'
Weight Lbs (loaded/empty)	2067/417



SNOWSTORM SPECS

SNOWFIRE QUICK ATTACH SPECS

SNOWSTORM QUICK
ATTACH SPECS

SHADOWBLADE SPECS

TRACTOR MOUNTS

KAGEKLAWZ SPECS


LIQUIDRAGE SPECS

ADVANTEDGE SPECS

WHEELKADDY SPECS

WHEELKADDY SPECS

ADVANTEDGE		
Part Name	Part Number	Length
SF AdvantEdge 6' Complete Kit	SFAEG	6 feet
SF AdvantEdge 8' Complete Kit	SFAEB	8 feet
SF AdvantEdge 9' Complete Kit	SFAE9	9 feet
SF AdvantEdge 10' Complete Kit	SFAEID	10 feet
SS AdvantEdge 12' Complete Kit	SSAE12	12 feet
SS AdvantEdge 14' Complete Kit	SSAE14	14 feet
SF AdvantEdge 2' Segment	SF2S	2 feet
SF AdvantEdge 3' Segment	SF3S	3 feet
SF AdvantEdge 4' Segment	SF4S	4 feet
SF AdvantEdge 5' Segment	SF5S	5 feet
AdvantEdge Replacement Cutting Edge 18"	SBC18FE	18 inches
AdvantEdge Replacement Cutting Edge 24"	SBC24FE	24 inches
Edge Extension 18	18EEKIT	18 inches
Edge Extension 24	24EEKIT	24 inches



WHEELKADDY FEATURE COMPARISON			
	250 Series	500 Series	360 Series
Soft-Ride Suspension		✓	\checkmark
3-Piece Wheels (quick tire change)	✓	✓	✓
360 Degree Pivot Action			\checkmark
Grade 50 Steel Platform	✓	✓	✓
Quick Release Mount	\checkmark	\checkmark	\checkmark
Tapered Roller Bearings	✓	\checkmark	✓
Grease-able P-T-O Pivots	\checkmark	\checkmark	\checkmark
Platform Pitch Adjustment	✓	\checkmark	✓
Standard Tire Diameter	13"	13"	10"-11"

WHEELKADDY SERIES SPECS					
	250 Series	500 Series	360 Series - 10" tires		
Tire Size	13" (13 x 5.00-6)	13" (13 x 5.00-6)	10" (410/350-4)		
Length Adjust	Adjustable 20" to 26"	Adjustable	Adjustable 21" to 25"		
Platform Height	3"	3"	1 3/4"		
Tire Width	4 1/2"	4 1/2"	3 7/8"		
Platform Width	26 3/4"	26 3/4"	26 1/4"		
Max. Mount Height	15 3/8"	15 3/8"	13 1/2"		
Min. Mount Height	9 3/8"	9 3/8"	12"		
Pitch Adjust	N/A	N/A	Adjustable +/- 3 Degrees from level height		
Weight	48 lbs.	48 lbs.	46.8 lbs.		
Wheel Bearing Type	Tapered Roller Bearing	Tapered Roller Bearing	Tapered Roller Bearing		
Oscillation	Yes	Yes	Yes		
Tire (Tubed/Tubeless)	Tubed	Tubed	Tubed		
360 Degree Pivot	N/A	N/A	Yes		
Suspension	N/A	Yes	Yes		

SNOWSTORM SPECS

SNOWFIRE QUICK ATTACH SPECS

SNOWSTORM QUICK
ATTACH SPECS

SHADDWBLADE SPECS

TRACTOR MOUNTS

KAGEKLAWZ SPECS



KAGE Innovation, LLC

KAGEInnovation.com | 651-433-4628 | fax 651-344-0887

502 Simmon Drive Osceola, WI 54020

PATENT INFORMATION
SNOWFIRE & SNOWSTORM - Patent #7.654.016: #7.788.829: #7.941.947: #2.707.963: #2.574.587
SHADOWBLADE - Patent # 8776406