

TRACTOR MOUNT *BOLT-ON UNDERCARRIAGES*

EVOLUTIONARY DESIGN

Let's have a conversation about the fuel efficiency of a tractor, the maneuverability of a tractor, the comforts of a tractor cab and the superior traction & power of a tractor.

Then let's talk about mounting the world's best plow on the front of that tractor. Now that's something worth talking about! KAGE has harnessed the versatility of using a tractor for snow plowing by designing a bolt-on undercarriage mount for their signature plow systems. Our tractor mounts are built to handle the rigors of massive snow removal.



"FLOAT MODE" FEATURE

< **FLOAT MODE** for ease of plowing over contoured surfaces yet maintains full down pressure



DIGITALLY PRECISE DESIGN



MORE VISIBILITY

With the low profile attachment of the undercarriage and KAGE Plow System, the tractor and plow are more maneuverable and visibility is vastly improved over the use of loader arms.

KAGE TRACTOR MOUNT SPECIFICATIONS

THE KAGE ADVANTAGE

With a KAGE Tractor Mount & KAGE Snow Plow System bolted onto the undercarriage of your tractor, you'll be able to push incredible amounts of snow. The undercarriage hitch system eliminates clumsy, dangerous loader arms and increases visibility.

UNDERCARRIAGE KITS

| MAKE/MODEL TRACTOR | PLOW HITCH STYLE | LIFT CYLINDERS | TRACTOR REQUIREMENTS | RECOMMENDED SYSTEM |
|--|------------------|----------------------------|--|--------------------|
| JOHN DEERE® - 6430/6125R/6125M/6115M | CAT II 3-POINT | (2) 4" X 10" | > LOADER VALVE/JOYSTICK IN CAB > ONE AUXILIARY (MID OR REAR) | 10', 12', 14' SS |
| JOHN DEERE® - 6410M/6150M | | | | |
| JOHN DEERE® - 5095M/5105M/5100M/5115M/5085M INCLUDES TIER 4 | | | > LOADER VALVE/JOYSTICK IN CAB > ONE AUXILIARY (MID OR REAR) > 800-1,000 LBS COUNTERWEIGHT RECOMMENDED | 10' SS OR 12' SF |
| JOHN DEERE® - 5101E/5083E/5085E* INCLUDES TIER 4 | | | | |
| JOHN DEERE® - 6101D/6115D/6130D/6140D ** | | | > JOYSTICK IN CAB > ONE AUXILIARY (MID OR REAR) | 10', 12', 14' SS |
| JOHN DEERE® - 6105D/6140D | | | | |
| KUBOTA® - L424D/L474D/L504D/L524D/L574D | 2-PIN STYLE | (1) 2-1/2" X 16" CYLINDERS | > JOYSTICK IN CAB W/ 3RD AUXILIARY OPTION > 800-1,000 LBS COUNTERWEIGHT RECOMMENDED | 8' SF |
| JOHN DEERE® - 412D/432D/452D/472D/4066R | | | | |
| KUBOTA® - M854D/M954D/M856D/M996D | CAT II 3-POINT | (2) 4" X 10" CYLINDERS | > LOADER VALVE/JOYSTICK IN CAB > ONE AUXILIARY (MID OR REAR) | 10' SS OR 12' SF |
| KUBOTA® M135X | | | | |
| KUBOTA® M110GX | | | | 10', 12', 14' SS |
| KUBOTA® M135GX | | | | |

MOST ORDERS SHIP WITHIN 2 WEEKS OR LESS. CALL FOR DETAILS

* VERIFY FOR 2010 MODELS. ASK YOUR SALESPERSON FOR MORE INFORMATION

** EXCLUDES TIER 4 ENGINES



TO ORDER CALL [651-433-4628](tel:651-433-4628), OR GO ONLINE: KAGEINNOVATION.COM