

UNDERCARRIAGE KITS

MAKE/MODEL TRACTOR	PLOW HITCH STYLE	LIFT CYLINDERS	TRACTOR REQUIREMENTS	RECOMMENDED SYSTEM
John Deere - 6430/6125R/6125M/6115M John Deere - 6410M/6150M	CAT II 3-Point	(2) 4" x 10"	>Loader valve/joystick in cab >One auxillary (mid or rear)	10', 12', 14' SS
John Deere - 5095M/5105M/5100M/5115M/5085M Includes Tier 4 John Deere 5101E/5083E/5085E * Includes Tier 4			>Loader valve/joystick in cab >One auxillary (mid or rear) >800-1,000 lbs counterweight recommended	10' SS or 12' SF
John Deere 6101D/6115D/6130D/6140D ** John Deere - 6105D/6140D			>Joystick in cab >One auxillary (mid or rear)	10', 12', 14' SS
Kubota - L4240/L4740/L5040/L5240/L5740 John Deere - 4120/4320/4520/4720/4066R			2-Pin Style	(1) 2-1/2" x 16" Cylinders
Kubota - M8540/M9540/M8560/M9960 Kubota M135X Kubota M110GX Kubota M135GX	CAT II 3-Point	(2) 4" x 10" Cylinders	>Loader valve/joystick in cab >One auxillary (mid or rear)	10' SS or 12' SF 10', 12', 14' SS

Most orders ship within 2 weeks or less, call for details

* Verify for 2010 models, ask your salesperson for more information

**Excludes tier 4 engines